



# I/O Connectors



C B O 12. 4 -2 - C B 12. 4 / P

**Special Function and Cable Material**

Null: PVC  
P: PUR  
WS: Shielded  
L: PNP LED  
LN: NPN LED  
EWSR: Welding spark resistance

**No. of Pin**

3: 3-pin  
4: 4-pin  
5: 5-pin  
8: 8-pin

**Size**

8: M8\*1 12: M12\*1

**Shape**

Null: Straight B: Angled

**Product Category**

C-type Q-type

**Specification**

Null: Single pre-wired

**Cable length**

Standard: 2m

**No. of Pin**

2: 2-pin(2.2, 2.21, 2.22 different pin sequence)  
3: 3-pin  
4: 4-pin  
5: 5-pin  
8: 8-pin

**Size**

8: M8\*1 12: M12\*1

**Gender**

Null: Male O: Female

**Shape**

Null: Straight B: Angled

**Product Category**

C-type Q-type

**Cordsets  
Order Code**

ECS - F E 2 C B . 12 . 4 - 2/2 / .

**Special Function and Cable Material**

Null: PVC  
 P: PUR  
 WS: Shielded  
 L: PNP LED  
 LN: NPN LED  
 B24: 2-, 4-pin shorted

**Connection Type (splitter)**

2/2: 2m cable for each end  
 2-C12.4: Male straight M12 connector with 2m cable  
 2-C8.4: Male straight M8 connector with 2m cable  
 2-CB12.4: Male angled M12 connector with 2m cable  
 2-CB8.4: Male angled M8 connector with 2m cable

**No. of Pin**

2: 2-pin(2.2, 2.21, 2.22 different pin sequence)  
 3: 3-pin  
 4: 4-pin  
 5: 5-pin

**Connection Type (adapter)**

Null: Homerun cable  
 8: M8\*1 12: M12\*1

**Gender**

Null: Male O: Female

**Shape**

Null: Straight B: Angled

**Specification**

Null: Homerun cable VC: Pre-wired connector

**Product Category**

Null: Y adapter 2: Y splitter

**Size**

Null: M12 E: M8

**Gender**

Null: Male F: Female

**Product Category**

Y splitter/adapter

**Y Splitter/Adapter  
 Order Code**

# Pre-Wired I/O Connectors

**The pre-wired and plastic I/O connectors meet all requirements for safe, fast and reliable field connections. Our standardized pre-wired connectors guarantee steady and shock prove IP67 connections. Depending on the selected cable type, they cover all applications in difficult environmental conditions like chemical influences, high or low air temperatures and significant mechanical stress. Cables are available with screening shields to ensure secure and interference-free signal transmissions.**

- Shock resistant, reliable contact
- 360° shielded connectors
- Protection class IP67
- Current rating 2-4 A (depends on number of cores )
- Optional 2, 3, 4, 5, 8 core cables available
- Various cable types:
  - PVC, PUR, with or without shields, EWSR spark resistant
  - STPE high elastic and high flexible
- Oil and chemical resistant, flame retardant, drag chain suitable
- Connectors M8x1, M12x1, 7/8", M23x1 threads
- Optional straight and angled connectors
- Built in LED indicators
- Optional A-coded, B-coded etc. interface
- Standard cable lengths 2m, all other lengths optionally available
- Special cables for special applications available on request



# Y Splitter/Adapter

***Y Splitter/Adapter includes different types of products, such as module type and cable output type. It can be used as simple distribution box and extended port access to reduce installation cost and save installation time. The material and structure of Y splitter/adapter are available in dirty and damp industrial environment and its protection class is up to IP67.***

***Y splitter/adapter including M12 to 2×M12, M12 to 2×M8, M8 to 2×M12, M8 to 2×M8 and M8/M12 to homerun cable with customized length. It can be used for port extension, distribution box kit and distributed I/O connector extension.***



# I/O Cable

## **PVC Cable** /

The cable with PVC jacket and its good mechanical performance (e.g. tensile strength, crack and abrasion resistance) is suitable for most applications in industrial installations. The cable is weatherproof and resistant to oil and chemical solutions. It is therefore a standard and economic solution for field installations to link I/O systems.

## **EWSR Cable** /

The special jacket material can enhance the mechanical properties (including tensile strength, crack resistance and wear resistance) and has high temperature resistance. Once you choose this cable, the detailed field environment and requirements must be clear.





















## **PUR Cable** /

The PUR jacket cable with its superior mechanical performance (e.g. tensile strength, crack and abrasion resistance, weather and oil/chemical resistance) is suitable for applications in extreme environments. It is therefore an ideal solution for industrial installations to link I/O systems in a harsh environment.








## **Shielding Cable** /

The tinned copper braid shielding layer provides a good electromagnetic shield against interferences. Shielded cables therefore improve safe signal transmissions. A wide range of special cables for special applications are available upon request. Please contact us to discuss your exact requirements.









### Pin Assignment

	2pin			3pin	4pin	5pin	8pin
	2.2	2.21	2.22				
M8 Female				4BK 3BU  1BN	4BK 2WH 3BU  1BN	5GY 3BU  1BN 4BK 2WH	
M8 Male				4BK 1BN  3BU	2WH 4BK 1BN  3BU	5GY 3BU  1BN 4BK 2WH	
M12 Female	1BN  4BU	2BU 1BN 	3BN 4BU 	2 1BN  3BU 4BK	2WH 1BN  3BU 4BK	2WH 1BN  3BU 5GY 4BK	
M12 Male	 1BN 4BU	2 BU  1BN	3BN  4BU	2 3BU  1BN 4BK	2WH 3BU  1BN 4BK	2WH 5GY 3BU  1BN 4BK	

### Dimensions M8

	Straight Female	Angled Female	Straight Male	Angled Male
Standard				
Special Application				
Y-Splitter				

### Dimensions M12

	Straight Female	Angled Female	Straight Male	Angled Male
Standard				
Special Application				
Y-Splitter				




A large yellow industrial robot arm is the central focus, positioned in a factory setting. The robot is mounted on a grey base and is surrounded by various cables and hoses. In the background, other similar robot arms and the skeletal frames of cars are visible, indicating an automotive manufacturing environment. The lighting is industrial, with a slightly dim, greyish-blue tint over the entire scene.





*I/O*

*Connectors*

*M12*

## Single-ended I/O Cordsets- M12 (Straight-female)

Type Code						
Cable jacket	Description	Type	Pin	Rated current/voltage	Cable length	Wire section
 PVC	Female DC 2-core	CO12.2-2	2	4A/250V	2m	0.34mm <sup>2</sup>
	Female AC/DC 2-core	CO12.21-2	2	4A/250V	2m	0.34mm <sup>2</sup>
	Female AC 2-core	CO12.22-2	2	4A/250V	2m	0.34mm <sup>2</sup>
	Female 3-core NO	CO12.3-2	3	4A/250V	2m	0.34mm <sup>2</sup>
	Female 3-core NO with LEDPNP	CO12.3-2/L	3	4A/30V	2m	0.34mm <sup>2</sup>
	Female 3-core NO with LEDNPN	CO12.3-2/LN	3	4A/30V	2m	0.34mm <sup>2</sup>
	Female 4-core NO/NC	CO12.4-2	4	4A/250V	2m	0.34mm <sup>2</sup>
	Female 4-core NO/NC with LEDPNP	CO12.4-2/L	4	4A/30V	2m	0.34mm <sup>2</sup>
	Female 4-core NO/NC with LEDNPN	CO12.4-2/LN	4	4A/30V	2m	0.34mm <sup>2</sup>
	Female 5-core NO/NC	CO12.5-2	5	4A/60V	2m	0.34mm <sup>2</sup>
	Female 8-core	CO12.8-2	8	2A/30V	2m	0.25mm <sup>2</sup>
PUR	Female DC 2-core	CO12.2-2/P	2	4A/250V	2m	0.34mm <sup>2</sup>
	Female AC/DC 2-core	CO12.21-2/P	2	4A/250V	2m	0.34mm <sup>2</sup>
	Female AC 2-core	CO12.22-2/P	2	4A/250V	2m	0.34mm <sup>2</sup>
	Female 3-core NO	CO12.3-2/P	3	4A/250V	2m	0.34mm <sup>2</sup>
	Female 3-core NO with LEDPNP	CO12.3-2/L/P	3	4A/30V	2m	0.34mm <sup>2</sup>
	Female 3-core NO with LEDNPN	CO12.3-2/LN/P	3	4A/30V	2m	0.34mm <sup>2</sup>
	Female 4-core NO/NC	CO12.4-2/P	4	4A/250V	2m	0.34mm <sup>2</sup>
	Female 4-core NO/NC with LEDPNP	CO12.4-2/L/P	4	4A/30V	2m	0.34mm <sup>2</sup>
	Female 4-core NO/NC with LEDNPN	CO12.4-2/LN/P	4	4A/30V	2m	0.34mm <sup>2</sup>
	Female 5-core NO/NC	CO12.5-2/P	5	4A/60V	2m	0.34mm <sup>2</sup>
	Female 8-core	CO12.8-2/P	8	2A/30V	2m	0.25mm <sup>2</sup>


Product with LED	PNP 3-core	NPN 3-core	PNP 4-core	NPN 4-core
				





## Single-ended I/O Cordsets- M12 (Straight-male)

Type Code						
Cable jacket	Description	Type	Pin	Rated current/voltage	Cable length	Wire section
PVC	Male DC 2-core	C12.2-2	2	4A/250V	2m	0.34mm <sup>2</sup>
	Male AC/DC 2-core	C12.21-2	2	4A/250V	2m	0.34mm <sup>2</sup>
	Male AC 2-core	C12.22-2	2	4A/250V	2m	0.34mm <sup>2</sup>
	Male 3-core NO	C12.3-2	3	4A/250V	2m	0.34mm <sup>2</sup>
	Male 4-core NO/NC	C12.4-2	4	4A/250V	2m	0.34mm <sup>2</sup>
	Male 5-core NO/NC	C12.5-2	5	4A/60V	2m	0.34mm <sup>2</sup>
	Male 8-core	C12.8-2	8	2A/30V	2m	0.25mm <sup>2</sup>
PUR	Male DC 2-core	C12.2-2/P	2	4A/250V	2m	0.34mm <sup>2</sup>
	Male AC/DC 2-core	C12.21-2/P	2	4A/250V	2m	0.34mm <sup>2</sup>
	Male AC 2-core	C12.22-2/P	2	4A/250V	2m	0.34mm <sup>2</sup>
	Male 3-core NO	C12.3-2/P	3	4A/250V	2m	0.34mm <sup>2</sup>
	Male 4-core NO/NC	C12.4-2/P	4	4A/250V	2m	0.34mm <sup>2</sup>
	Male 5-core NO/NC	C12.5-2/P	5	4A/60V	2m	0.34mm <sup>2</sup>
	Male 8-core	C12.8-2/P	8	2A/30V	2m	0.25mm <sup>2</sup>




## Single-ended I/O Cordsets-M12 (Angled-female)


Type Code						
Cable jacket	Description	Type	Pin	Rated current/voltage	Cable length	Wire section
 PVC	Female DC 2-core	CBO12.2-2	2	4A/250V	2m	0.34mm <sup>2</sup>
	Female AC/DC 2-core	CBO12.21-2	2	4A/250V	2m	0.34mm <sup>2</sup>
	Female AC 2-core	CBO12.22-2	2	4A/250V	2m	0.34mm <sup>2</sup>
	Female 3-core NO	CBO12.3-2	3	4A/250V	2m	0.34mm <sup>2</sup>
	Female 3-core NO with LEDPNP	CBO12.3-2/L	3	4A/30V	2m	0.34mm <sup>2</sup>
	Female 3-core NO with LEDNPN	CBO12.3-2/LN	3	4A/30V	2m	0.34mm <sup>2</sup>
	Female 4-core NO/NC	CBO12.4-2	4	4A/250V	2m	0.34mm <sup>2</sup>
	Female 4-core NO/NC with LEDPNP	CBO12.4-2/L	4	4A/30V	2m	0.34mm <sup>2</sup>
	Female 4-core NO/NC with LEDNPN	CBO12.4-2/LN	4	4A/30V	2m	0.34mm <sup>2</sup>
	Female 5-core NO/NC	CBO12.5-2	5	4A/60V	2m	0.34mm <sup>2</sup>
	Female 8-core	CBO12.8-2	8	2A/30V	2m	0.25mm <sup>2</sup>
PUR	Female DC 2-core	CBO12.2-2/P	2	4A/250V	2m	0.34mm <sup>2</sup>
	Female AC/DC 2-core	CBO12.21-2/P	2	4A/250V	2m	0.34mm <sup>2</sup>
	Female AC 2-core	CBO12.22-2/P	2	4A/250V	2m	0.34mm <sup>2</sup>
	Female 3-core NO	CBO12.3-2/P	3	4A/250V	2m	0.34mm <sup>2</sup>
	Female 3-core NO with LEDPNP	CBO12.3-2/L/P	3	4A/30V	2m	0.34mm <sup>2</sup>
	Female 3-core NO with LEDNPN	CBO12.3-2/LN/P	3	4A/30V	2m	0.34mm <sup>2</sup>
	Female 4-core NO/NC	CBO12.4-2/P	4	4A/250V	2m	0.34mm <sup>2</sup>
	Female 4-core NO/NC with LEDPNP	CBO12.4-2/L/P	4	4A/30V	2m	0.34mm <sup>2</sup>
	Female 4-core NO/NC with LEDNPN	CBO12.4-2/LN/P	4	4A/30V	2m	0.34mm <sup>2</sup>
	Female 5-core NO/NC	CBO12.5-2/P	5	4A/60V	2m	0.34mm <sup>2</sup>
	Female 8-core	CBO12.8-2/P	8	2A/30V	2m	0.25mm <sup>2</sup>

Product with LED	PNP 3-core	NPN 3-core	PNP 4-core	NPN 4-core
				


## Single-ended I/O Cordsets-M12 (Angled-male)

Type Code						
Cable jacket	Description	Type	Pin	Rated current/voltage	Cable length	Wire section
 PVC	Male DC 2-core	CB12.2-2	2	4A/250V	2m	0.34mm <sup>2</sup>
	Male AC/DC 2-core	CB12.21-2	2	4A/250V	2m	0.34mm <sup>2</sup>
	Male AC 2-core	CB12.22-2	2	4A/250V	2m	0.34mm <sup>2</sup>
	Male 3-core NO	CB12.3-2	3	4A/250V	2m	0.34mm <sup>2</sup>
	Male 4-core NO/NC	CB12.4-2	4	4A/250V	2m	0.34mm <sup>2</sup>
	Male 5-core NO/NC	CB12.5-2	5	4A/60V	2m	0.34mm <sup>2</sup>
	Male 8-core	CB12.8-2	8	2A/30V	2m	0.25mm <sup>2</sup>
PUR	Male DC 2-core	CB12.2-2/P	2	4A/250V	2m	0.34mm <sup>2</sup>
	Male AC/DC 2-core	CB12.21-2/P	2	4A/250V	2m	0.34mm <sup>2</sup>
	Male AC 2-core	CB12.22-2/P	2	4A/250V	2m	0.34mm <sup>2</sup>
	Male 3-core NO	CB12.3-2/P	3	4A/250V	2m	0.34mm <sup>2</sup>
	Male 4-core NO/NC	CB12.4-2/P	4	4A/250V	2m	0.34mm <sup>2</sup>
	Male 5-core NO/NC	CB12.5-2/P	5	4A/60V	2m	0.34mm <sup>2</sup>
	Male 8-core	CB12.8-2/P	8	2A/30V	2m	0.25mm <sup>2</sup>

## Single-ended I/O Cordsets-M12 (Straight-female)

Type Code							
Cable jacket	Description	Type	Pin	Rated current/voltage	Cable length	Wire section	
	Welding spark resistance	Female 3-core	CO12.3-2/EWSR	3	4A/250V	2m	0.34mm <sup>2</sup>
		Female 4-core	CO12.4-2/EWSR	4	4A/250V	2m	0.34mm <sup>2</sup>
		Female 5-core	CO12.5-2/EWSR	5	4A/60V	2m	0.34mm <sup>2</sup>
PVC Shielded	Female 3-core	CO12.3-2/WS	3	4A/250V	2m	0.34mm <sup>2</sup>	
	Female 4-core	CO12.4-2/WS	4	4A/250V	2m	0.34mm <sup>2</sup>	
	Female 5-core	CO12.5-2/WS	5	4A/60V	2m	0.34mm <sup>2</sup>	
	Female 8-core	CO12.8-2/WS	8	2A/30V	2m	0.25mm <sup>2</sup>	
PUR Shielded	Female 3-core	CO12.3-2/WS/P	3	4A/250V	2m	0.34mm <sup>2</sup>	
	Female 4-core	CO12.4-2/WS/P	4	4A/250V	2m	0.34mm <sup>2</sup>	
	Female 5-core	CO12.5-2/WS/P	5	4A/60V	2m	0.34mm <sup>2</sup>	
	Female 8-core	CO12.8-2/WS/P	8	2A/30V	2m	0.25mm <sup>2</sup>	
	Female 12-core	CO12.12-2/WS/P	12	1.5A/30V	2m	0.25mm <sup>2</sup>	

## Single-ended I/O Cordsets-M12 (Straight-male)

Type Code							
	Cable jacket	Description	Type	Pin	Rated current/voltage	Cable length	Wire section
	Welding spark resistance	Male 3-core	C12.3-2/EWSR	3	4A/250V	2m	0.34mm <sup>2</sup>
		Male 4-core	C12.4-2/EWSR	4	4A/250V	2m	0.34mm <sup>2</sup>
		Male 5-core	C12.5-2/EWSR	5	4A/60V	2m	0.34mm <sup>2</sup>
	PVC Shielded	Male 3-core	C12.3-2/WS	3	4A/250V	2m	0.34mm <sup>2</sup>
		Male 4-core	C12.4-2/WS	4	4A/250V	2m	0.34mm <sup>2</sup>
		Male 5-core	C12.5-2/WS	5	4A/60V	2m	0.34mm <sup>2</sup>
		Male 8-core	C12.8-2/WS	8	2A/30V	2m	0.25mm <sup>2</sup>
	PUR Shielded	Male 3-core	C12.3-2/WS/P	3	4A/250V	2m	0.34mm <sup>2</sup>
		Male 4-core	C12.4-2/WS/P	4	4A/250V	2m	0.34mm <sup>2</sup>
		Male 5-core	C12.5-2/WS/P	5	4A/60V	2m	0.34mm <sup>2</sup>
		Male 8-core	C12.8-2/WS/P	8	2A/30V	2m	0.25mm <sup>2</sup>

## Single-ended I/O Cordsets-M12 (Angled-female)

Type Code						
Cable jacket	Description	Type	Pin	Rated current/voltage	Cable length	Wire section
Welding spark resistance	Female 3-core	CBO12.3-2/EWSR	3	4A/250V	2m	0.34mm <sup>2</sup>
	Female 4-core	CBO12.4-2/EWSR	4	4A/250V	2m	0.34mm <sup>2</sup>
	Female 5-core	CBO12.5-2/EWSR	5	4A/60V	2m	0.34mm <sup>2</sup>
PVC Shielded	Female 3-core	CBO12.3-2/WS	3	4A/250V	2m	0.34mm <sup>2</sup>
	Female 4-core	CBO12.4-2/WS	4	4A/250V	2m	0.34mm <sup>2</sup>
	Female 5-core	CBO12.5-2/WS	5	4A/60V	2m	0.34mm <sup>2</sup>
	Female 8-core	CBO12.8-2/WS	8	2A/30V	2m	0.25mm <sup>2</sup>
PUR Shielded	Female 3-core	CBO12.3-2/WS/P	3	4A/250V	2m	0.34mm <sup>2</sup>
	Female 4-core	CBO12.4-2/WS/P	4	4A/250V	2m	0.34mm <sup>2</sup>
	Female 5-core	CBO12.5-2/WS/P	5	4A/60V	2m	0.34mm <sup>2</sup>
	Female 8-core	CBO12.8-2/WS/P	8	2A/30V	2m	0.25mm <sup>2</sup>







## Single-ended I/O Cordsets-M12 (Angled-male)



Type Code						
Cable jacket	Description	Type	Pin	Rated current/voltage	Cable length	Wire section
Welding spark resistance	Male 3-core	CB12.3-2/EWSR	3	4A/250V	2m	0.34mm <sup>2</sup>
	Male 4-core	CB12.4-2/EWSR	4	4A/250V	2m	0.34mm <sup>2</sup>
	Male 5-core	CB12.5-2/EWSR	5	4A/60V	2m	0.34mm <sup>2</sup>
PVC Shielded	Male 3-core	CB12.3-2/WS	3	4A/250V	2m	0.34mm <sup>2</sup>
	Male 4-core	CB12.4-2/WS	4	4A/250V	2m	0.34mm <sup>2</sup>
	Male 5-core	CB12.5-2/WS	5	4A/60V	2m	0.34mm <sup>2</sup>
	Male 8-core	CB12.8-2/WS	8	2A/30V	2m	0.25mm <sup>2</sup>
PUR Shielded	Male 3-core	CB12.3-2/WS/P	3	4A/250V	2m	0.34mm <sup>2</sup>
	Male 4-core	CB12.4-2/WS/P	4	4A/250V	2m	0.34mm <sup>2</sup>
	Male 5-core	CB12.5-2/WS/P	5	4A/60V	2m	0.34mm <sup>2</sup>
	Male 8-core	CB12.8-2/WS/P	8	2A/30V	2m	0.25mm <sup>2</sup>





## Double-ended I/O Cordsets-M12 (female) to M12 (male)

Type Code							
	Cable jacket	Description	Type	Pin	Rated current/voltage	Cable length	Wire section
	PVC	3-core straight to straight	CO12.3-2-C12.3	3	4A/250V	2m	0.34mm <sup>2</sup>
		3-core straight to angled	CO12.3-2-CB12.3	3	4A/250V	2m	0.34mm <sup>2</sup>
		4-core straight to straight	CO12.4-2-C12.4	4	4A/250V	2m	0.34mm <sup>2</sup>
		4-core straight to angled	CO12.4-2-CB12.4	4	4A/250V	2m	0.34mm <sup>2</sup>
		5-core straight to straight	CO12.5-2-C12.5	5	4A/60V	2m	0.34mm <sup>2</sup>
		5-core straight to angled	CO12.5-2-CB12.5	5	4A/60V	2m	0.34mm <sup>2</sup>
	PUR	3-core straight to straight	CO12.3-2-C12.3/P	3	4A/250V	2m	0.34mm <sup>2</sup>
		3-core straight to angled	CO12.3-2-CB12.3/P	3	4A/250V	2m	0.34mm <sup>2</sup>
		4-core straight to straight	CO12.4-2-C12.4/P	4	4A/250V	2m	0.34mm <sup>2</sup>
		4-core straight to angled	CO12.4-2-CB12.4/P	4	4A/250V	2m	0.34mm <sup>2</sup>
		5-core straight to straight	CO12.5-2-C12.5/P	5	4A/60V	2m	0.34mm <sup>2</sup>
		5-core straight to angled	CO12.5-2-CB12.5/P	5	4A/60V	2m	0.34mm <sup>2</sup>



## Double-ended I/O Cordsets-M12 (female) to M12 (male)

Type Code							
	Cable jacket	Description	Type	Pin	Rated current/voltage	Cable length	Wire section
	PVC	3-core angled to straight	CBO12.3-2-C12.3	3	4A/250V	2m	0.34mm <sup>2</sup>
		3-core angled to angled	CBO12.3-2-CB12.3	3	4A/250V	2m	0.34mm <sup>2</sup>
		4-core angled to straight	CBO12.4-2-C12.4	4	4A/250V	2m	0.34mm <sup>2</sup>
		4-core angled to angled	CBO12.4-2-CB12.4	4	4A/250V	2m	0.34mm <sup>2</sup>
		5-core angled to straight	CBO12.5-2-C12.5	5	4A/60V	2m	0.34mm <sup>2</sup>
		5-core angled to angled	CBO12.5-2-CB12.5	5	4A/60V	2m	0.34mm <sup>2</sup>
	PUR	3-core angled to straight	CBO12.3-2-C12.3/P	3	4A/250V	2m	0.34mm <sup>2</sup>
		3-core angled to angled	CBO12.3-2-CB12.3/P	3	4A/250V	2m	0.34mm <sup>2</sup>
		4-core angled to straight	CBO12.4-2-C12.4/P	4	4A/250V	2m	0.34mm <sup>2</sup>
		4-core angled to angled	CBO12.4-2-CB12.4/P	4	4A/250V	2m	0.34mm <sup>2</sup>
		5-core angled to straight	CBO12.5-2-C12.5/P	5	4A/60V	2m	0.34mm <sup>2</sup>
		5-core angled to angled	CBO12.5-2-CB12.5/P	5	4A/60V	2m	0.34mm <sup>2</sup>


## Double-ended I/O Cordsets-M12 (female) to M8 (male)





Type Code							
	Cable jacket	Description	Type	Pin	Rated current/voltage	Cable length	Wire section
	PVC	3-core straight to straight	CO12.3-2-C8.3	3	4A/60V	2m	0.25mm <sup>2</sup>
		3-core straight to angled	CO12.3-2-CB8.3	3	4A/60V	2m	0.25mm <sup>2</sup>
		4-core straight to straight	CO12.4-2-C8.4	4	4A/30V	2m	0.25mm <sup>2</sup>
		4-core straight to angled	CBO12.4-2-CB8.4	4	4A/30V	2m	0.25mm <sup>2</sup>
	PUR	3-core straight to straight	CO12.3-2-C8.3/P	3	4A/60V	2m	0.25mm <sup>2</sup>
		3-core straight to angled	CO12.3-2-CB8.3/P	3	4A/60V	2m	0.25mm <sup>2</sup>
		4-core straight to straight	CO12.4-2-C8.4/P	4	4A/30V	2m	0.25mm <sup>2</sup>
		4-core straight to angled	CO12.4-2-CB8.4/P	4	4A/30V	2m	0.25mm <sup>2</sup>

## Double-ended I/O Cordsets-M12 (female) to M8 (male)


Type Code							
	Cable jacket	Description	Type	Pin	Rated current/voltage	Cable length	Wire section
	PVC	3-core angled to straight	CBO12.3-2-CB8.3	3	4A/60V	2m	0.25mm <sup>2</sup>
		3-core angled to angled	CBO12.3-2-CB8.3	3	4A/60V	2m	0.25mm <sup>2</sup>
		4-core angled to straight	CBO12.4-2-CB8.4	4	4A/30V	2m	0.25mm <sup>2</sup>
		4-core angled to angled	CBO12.4-2-CB8.4	4	4A/30V	2m	0.25mm <sup>2</sup>
	PUR	3-core angled to straight	CBO12.3-2-CB8.3/P	3	4A/60V	2m	0.25mm <sup>2</sup>
		3-core angled to angled	CBO12.3-2-CB8.3/P	3	4A/60V	2m	0.25mm <sup>2</sup>
		4-core angled to straight	CBO12.4-2-CB8.4/P	4	4A/30V	2m	0.25mm <sup>2</sup>
		4-core angled to angled	CBO12.4-2-CB8.4/P	4	4A/30V	2m	0.25mm <sup>2</sup>





## Double-ended I/O Cordsets-M12 (female) to M12 (male)

Type Code							
	Cable jacket	Description	Type	Pin	Rated current/voltage	Cable length	Wire section
	PVC	3-core straight to straight LEDPNP	CO12.3-2-C12.3/L	3	4A/30V	2m	0.34mm <sup>2</sup>
		3-core straight to angled LEDPNP	CO12.3-2-CB12.3/L	3	4A/30V	2m	0.34mm <sup>2</sup>
		4-core straight to straight LEDPNP	CO12.4-2-C12.4/L	4	4A/30V	2m	0.34mm <sup>2</sup>
		4-core straight to angled LEDPNP	CO12.4-2-CB12.4/L	4	4A/30V	2m	0.34mm <sup>2</sup>
		3-core straight to straight LEDNPN	CO12.3-2-C12.3/LN	3	4A/30V	2m	0.34mm <sup>2</sup>
		3-core straight to angled LEDNPN	CO12.3-2-CB12.3/LN	3	4A/30V	2m	0.34mm <sup>2</sup>
		4-core straight to straight LEDNPN	CO12.4-2-C12.4/LN	4	4A/30V	2m	0.34mm <sup>2</sup>
		4-core straight to angled LEDNPN	CO12.4-2-CB12.4/LN	4	4A/30V	2m	0.34mm <sup>2</sup>
	PUR	3-core straight to straight LEDPNP	CO12.3-2-C12.3/L/P	3	4A/30V	2m	0.34mm <sup>2</sup>
		3-core straight to angled LEDPNP	CO12.3-2-CB12.3/L/P	3	4A/30V	2m	0.34mm <sup>2</sup>
		4-core straight to straight LEDPNP	CO12.4-2-C12.4/L/P	4	4A/30V	2m	0.34mm <sup>2</sup>
		4-core straight to angled LEDPNP	CO12.4-2-CB12.4/L/P	4	4A/30V	2m	0.34mm <sup>2</sup>
		3-core straight to straight LEDNPN	CO12.3-2-C12.3/LN/P	3	4A/30V	2m	0.34mm <sup>2</sup>
		3-core straight to angled LEDNPN	CO12.3-2-CB12.3/LN/P	3	4A/30V	2m	0.34mm <sup>2</sup>
		4-core straight to straight LEDNPN	CO12.4-2-C12.4/LN/P	4	4A/30V	2m	0.34mm <sup>2</sup>
		4-core straight to angled LEDNPN	CO12.4-2-CB12.4/LN/P	4	4A/30V	2m	0.34mm <sup>2</sup>


Product with LED	PNP 3-core	NPN 3-core	PNP 4-core	NPN 4-core
				





## Double-ended I/O Cordsets-M12 (female) to M12 (male)

Type Code							
	Cable jacket	Description	Type	Pin	Rated current/voltage	Cable length	Wire section
	PVC	3-core angled to straight LEDPNP	CBO12.3-2-C12.3/L	3	4A/30V	2m	0.25mm <sup>2</sup>
		3-core angled to angled LEDPNP	CBO12.3-2-CB12.3/L	3	4A/30V	2m	0.25mm <sup>2</sup>
		4-core angled to straight LEDPNP	CBO12.4-2-C12.4/L	4	4A/30V	2m	0.25mm <sup>2</sup>
		4-core angled to angled LEDPNP	CBO12.4-2-CB12.4/L	4	4A/30V	2m	0.25mm <sup>2</sup>
		3-core angled to straight LEDNPN	CBO12.3-2-C12.3/LN	3	4A/30V	2m	0.25mm <sup>2</sup>
		3-core angled to angled LEDNPN	CBO12.3-2-CB12.3/LN	3	4A/30V	2m	0.25mm <sup>2</sup>
		4-core angled to straight LEDNPN	CBO12.4-2-C12.4/LN	4	4A/30V	2m	0.25mm <sup>2</sup>
		4-core angled to angled LEDNPN	CBO12.4-2-CB12.4/LN	4	4A/30V	2m	0.25mm <sup>2</sup>
	PUR	3-core angled to straight LEDPNP	CBO12.3-2-C12.3/L/P	3	4A/30V	2m	0.25mm <sup>2</sup>
		3-core angled to angled LEDPNP	CBO12.3-2-CB12.3/L/P	3	4A/30V	2m	0.25mm <sup>2</sup>
		4-core angled to straight LEDPNP	CBO12.4-2-C12.4/L/P	4	4A/30V	2m	0.25mm <sup>2</sup>
		4-core angled to angled LEDPNP	CBO12.4-2-CB12.4/L/P	4	4A/30V	2m	0.25mm <sup>2</sup>
		3-core angled to straight LEDNPN	CBO12.3-2-C12.3/LN/P	3	4A/30V	2m	0.25mm <sup>2</sup>
		3-core angled to angled LEDNPN	CBO12.3-2-CB12.3/LN/P	3	4A/30V	2m	0.25mm <sup>2</sup>
		4-core angled to straight LEDNPN	CBO12.4-2-C12.4/LN/P	4	4A/30V	2m	0.25mm <sup>2</sup>
		4-core angled to angled LEDNPN	CBO12.4-2-CB12.4/LN/P	4	4A/30V	2m	0.25mm <sup>2</sup>

Product with LED	PNP 3-core	NPN 3-core	PNP 4-core	NPN 4-core
				


## Double-ended I/O Cordsets-M12 (female) to M8 (male)





Type Code							
	Cable jacket	Description	Type	Pin	Rated current/voltage	Cable length	Wire section
	PVC	3-core straight to straight LEDPNP	CO12.3-2-C8.3/L	3	4A/30V	2m	0.25mm <sup>2</sup>
		3-core straight to angled LEDPNP	CO12.3-2-CB8.3/L	3	4A/30V	2m	0.25mm <sup>2</sup>
		4-core straight to straight LEDPNP	CO12.4-2-C8.4/L	4	4A/30V	2m	0.25mm <sup>2</sup>
		4-core straight to angled LEDPNP	CO12.4-2-CB8.4/L	4	4A/30V	2m	0.25mm <sup>2</sup>
		3-core straight to straight LEDNPN	CO12.3-2-C8.3/LN	3	4A/30V	2m	0.25mm <sup>2</sup>
		3-core straight to angled LEDNPN	CO12.3-2-CB8.3/LN	3	4A/30V	2m	0.25mm <sup>2</sup>
		4-core straight to straight LEDNPN	CO12.4-2-C8.4/LN	4	4A/30V	2m	0.25mm <sup>2</sup>
		4-core straight to angled LEDNPN	CO12.4-2-CB8.4/LN	4	4A/30V	2m	0.25mm <sup>2</sup>
	PUR	3-core straight to straight LEDPNP	CO12.3-2-C8.3/L/P	3	4A/30V	2m	0.25mm <sup>2</sup>
		3-core straight to angled LEDPNP	CO12.3-2-CB8.3/L/P	3	4A/30V	2m	0.25mm <sup>2</sup>
		4-core straight to straight LEDPNP	CO12.4-2-C8.4/L/P	4	4A/30V	2m	0.25mm <sup>2</sup>
		4-core straight to angled LEDPNP	CO12.4-2-CB8.4/L/P	4	4A/30V	2m	0.25mm <sup>2</sup>
		3-core straight to straight LEDNPN	CO12.3-2-C8.3/LN/P	3	4A/30V	2m	0.25mm <sup>2</sup>
		3-core straight to angled LEDNPN	CO12.3-2-CB8.3/LN/P	3	4A/30V	2m	0.25mm <sup>2</sup>
		4-core straight to straight LEDNPN	CO12.4-2-C8.4/LN/P	4	4A/30V	2m	0.25mm <sup>2</sup>
		4-core straight to angled LEDNPN	CO12.4-2-CB8.4/LN/P	4	4A/30V	2m	0.25mm <sup>2</sup>

Product with LED	PNP 3-core	NPN 3-core	PNP 4-core	NPN 4-core
				







## Double-ended I/O Cordsets-M12 (female) to M8 (male)

Type Code							
	Cable jacket	Description	Type	Pin	Rated current/voltage	Cable length	Wire section
	PVC	3-core angled to straight LEDPNP	CBO12.3-2-C8.3/L	3	4A/30V	2m	0.25mm <sup>2</sup>
		3-core angled to angled LEDPNP	CBO12.3-2-CB8.3/L	3	4A/30V	2m	0.25mm <sup>2</sup>
		4-core angled to straight LEDPNP	CBO12.4-2-C8.4/L	4	4A/30V	2m	0.25mm <sup>2</sup>
		4-core angled to angled LEDPNP	CBO12.4-2-CB8.4/L	4	4A/30V	2m	0.25mm <sup>2</sup>
		3-core angled to straight LEDNPN	CBO12.3-2-C8.3/LN	3	4A/30V	2m	0.25mm <sup>2</sup>
		3-core angled to angled LEDNPN	CBO12.3-2-CB8.3/LN	3	4A/30V	2m	0.25mm <sup>2</sup>
		4-core angled to straight LEDNPN	CBO12.4-2-C8.4/LN	4	4A/30V	2m	0.25mm <sup>2</sup>
		4-core angled to angled LEDNPN	CBO12.4-2-CB8.4/LN	4	4A/30V	2m	0.25mm <sup>2</sup>
	PUR	3-core angled to straight LEDPNP	CBO12.3-2-C8.3/L/P	3	4A/30V	2m	0.25mm <sup>2</sup>
		3-core angled to angled LEDPNP	CBO12.3-2-CB8.3/L/P	3	4A/30V	2m	0.25mm <sup>2</sup>
		4-core angled to straight LEDPNP	CBO12.4-2-C8.4/L/P	4	4A/30V	2m	0.25mm <sup>2</sup>
		4-core angled to angled LEDPNP	CBO12.4-2-CB8.4/L/P	4	4A/30V	2m	0.25mm <sup>2</sup>
		3-core angled to straight LEDNPN	CBO12.3-2-C8.3/LN/P	3	4A/30V	2m	0.25mm <sup>2</sup>
		3-core angled to angled LEDNPN	CBO12.3-2-CB8.3/LN/P	3	4A/30V	2m	0.25mm <sup>2</sup>
		4-core angled to straight LEDNPN	CBO12.4-2-C8.4/LN/P	4	4A/30V	2m	0.25mm <sup>2</sup>
		4-core angled to angled LEDNPN	CBO12.4-2-CB8.4/LN/P	4	4A/30V	2m	0.25mm <sup>2</sup>



Product with LED	PNP 3-core	NPN 3-core	PNP 4-core	NPN 4-core
				

## Y Splitter M12-male to M12-female

Type Code							
	Cable jacket	Description	Type	Pin	Rated current/voltage	Cable length	Wire section
	PVC	Straight to 2 straight	ECS-2CO12.4-2/2	4-3/3	4A/250V	2m	0.34mm <sup>2</sup>
		Straight to 2 angled	ECS-2CBO12.4-2/2	4-3/3	4A/250V	2m	0.34mm <sup>2</sup>
		Straight to 2 straight	ECS-2CO12.4-2/2/B24	4-4/4	4A/60V	2m	0.34mm <sup>2</sup>
		Straight to 2 angled	ECS-2CBO12.4-2/2/B24	4-4/4	4A/60V	2m	0.34mm <sup>2</sup>
	PUR	Straight to 2 straight	ECS-2CO12.4-2/2/P	4-3/3	4A/250V	2m	0.34mm <sup>2</sup>
		Straight to 2 angled	ECS-2CBO12.4-2/2/P	4-3/3	4A/250V	2m	0.34mm <sup>2</sup>
		Straight to 2 straight	ECS-2CO12.4-2/2/B24/P	4-4/4	4A/60V	2m	0.34mm <sup>2</sup>
		Straight to 2 angled	ECS-2CBO12.4-2/2/B24/P	4-4/4	4A/60V	2m	0.34mm <sup>2</sup>


Wiring Diagram	Standard	B24
		

## Y Splitter M12-male to M8-female



Type Code							
	Cable jacket	Description	Type	Pin	Rated current/voltage	Cable length	Wire section
	PVC	Straight to 2 straight	ECS-2CO8.3-2/2	4-3/3	4A/60V	2m	0.25mm <sup>2</sup>
		Straight to 2 angled	ECS-2CBO8.3-2/2	4-3/3	4A/60V	2m	0.25mm <sup>2</sup>
	PUR	Straight to 2 straight	ECS-2CO8.3-2/2/P	4-3/3	4A/60V	2m	0.25mm <sup>2</sup>
		Straight to 2 angled	ECS-2CBO8.3-2/2/P	4-3/3	4A/60V	2m	0.25mm <sup>2</sup>


### Wiring Diagram

### Standard






## Y Splitter M12-male to M12-female

Type Code							
	Cable jacket	Description	Type	Pin	Rated current/voltage	Cable length	Wire section
	PVC	Straight to 2 straight PNP	ECS-2CO12.4-2/2/L	4-3/3	4A/30V	2m	0.34mm <sup>2</sup>
		Straight to 2 angled PNP	ECS-2CBO12.4-2/2/L	4-3/3	4A/30V	2m	0.34mm <sup>2</sup>
		Straight to 2 straight NPN	ECS-2CO12.4-2/2/LN	4-3/3	4A/30V	2m	0.34mm <sup>2</sup>
		Straight to 2 angled NPN	ECS-2CBO12.4-2/2/LN	4-3/3	4A/30V	2m	0.34mm <sup>2</sup>
	PUR	Straight to 2 straight PNP	ECS-2CO12.4-2/2/L/P	4-3/3	4A/30V	2m	0.34mm <sup>2</sup>
		Straight to 2 angled PNP	ECS-2CBO12.4-2/2/L/P	4-3/3	4A/30V	2m	0.34mm <sup>2</sup>
		Straight to 2 straight NPN	ECS-2CO12.4-2/2/LN/P	4-3/3	4A/30V	2m	0.34mm <sup>2</sup>
		Straight to 2 angled NPN	ECS-2CBO12.4-2/2/LN/P	4-3/3	4A/30V	2m	0.34mm <sup>2</sup>




## Y Splitter M12-male to M8-female

Type Code							
	Cable jacket	Description	Type	Pin	Rated current/voltage	Cable length	Wire section
	PVC	Straight to 2 straight PNP	ECS-2CO8.3-2/2/L	4-3/3	4A/30V	2m	0.25mm <sup>2</sup>
		Straight to 2 angled PNP	ECS-2CBO8.3-2/2/L	4-3/3	4A/30V	2m	0.25mm <sup>2</sup>
		Straight to 2 straight NPN	ECS-2CO8.3-2/2/LN	4-3/3	4A/30V	2m	0.25mm <sup>2</sup>
		Straight to 2 angled NPN	ECS-2CBO8.3-2/2/LN	4-3/3	4A/30V	2m	0.25mm <sup>2</sup>
	PUR	Straight to 2 straight PNP	ECS-2CO8.3-2/2/L/P	4-3/3	4A/30V	2m	0.25mm <sup>2</sup>
		Straight to 2 angled PNP	ECS-2CBO8.3-2/2/L/P	4-3/3	4A/30V	2m	0.25mm <sup>2</sup>
		Straight to 2 straight NPN	ECS-2CO8.3-2/2/LN/P	4-3/3	4A/30V	2m	0.25mm <sup>2</sup>
		Straight to 2 angled NPN	ECS-2CBO8.3-2/2/LN/P	4-3/3	4A/30V	2m	0.25mm <sup>2</sup>




## Y Splitter M12(M) to Homerun Cable


Type Code							
	Cable jacket	Description	Type	Pin	Rated current/voltage	Cable length	Wire section
	PVC	Y Splitter M12(M) to Homerun Cable	ECS-2.3-2/2	4-3/3	4A/250V	2m	0.34mm <sup>2</sup>
	PUR	Y Splitter M12(M) to Homerun Cable	ECS-2.3-2/2/P	4-3/3	4A/250V	2m	0.34mm <sup>2</sup>

Wiring Diagram


Standard



## Y Adapter


Type Code						
Cable jacket	Description	Type	Pin	Rated current/voltage	Cable length	
	Universal Y adapter	ECS-CO12.3	4-3/3	4A/60V	—	
	Universal Y adapter	ECS-CO8.3	4-3/3	4A/60V	—	
Special	Special Y adapter	ECS-CO12.5	5-5/5	4A/60V	—	
	Special Y adapter	ECS-CO12.5/B24	5-4/4	4A/60V	—	

### Dimensions




### Wiring Diagram


Universal 4-3




Universal 5-5




Special 5-4(B24)



## Y Adapter with Cable


Type Code							
Cable jacket	Description	Type	Pin	Rated current/voltage	Cable length	Wire section	
	M12 male straight	ECS-CO12.3-2-C12.4	4-3/3	4A/60V	2m	0.34mm <sup>2</sup>	
	M8 male straight	ECS-CO12.3-2-C8.4	4-3/3	4A/60V	2m	0.25mm <sup>2</sup>	
	M12 male angled	ECS-CO12.3-2-CB12.4	4-3/3	4A/60V	2m	0.34mm <sup>2</sup>	
	M8 male angled	ECS-CO12.3-2-CB8.4	4-3/3	4A/60V	2m	0.25mm <sup>2</sup>	
Special Y adapter PUR	M12 male straight	ECS-CO12.3-2-C12.4/P	4-3/3	4A/60V	2m	0.34mm <sup>2</sup>	
	M8 male straight	ECS-CO12.3-2-C8.4/P	4-3/3	4A/60V	2m	0.25mm <sup>2</sup>	
	M12 male angled	ECS-CO12.3-2-CB12.4/P	4-3/3	4A/60V	2m	0.34mm <sup>2</sup>	
	M8 male angled	ECS-CO12.3-2-CB8.4/P	4-3/3	4A/60V	2m	0.25mm <sup>2</sup>	

### Dimensions



### Wiring Diagram

Universal 4-3












**I/O**

**Connectors**


**M8**

## Single-ended I/O Cordsets-M8 (Straight-female)

Type Code						
Cable jacket	Description	Type	Pin	Rated current/voltage	Cable length	Wire section
 PVC	Female 3-core	CO8.3-2	3	4A/60V	2m	0.25mm <sup>2</sup>
	Female 4-core	CO8.4-2	4	4A/30V	2m	0.25mm <sup>2</sup>
	Female 3-core PNP	CO8.3-2/L	3	4A/30V	2m	0.25mm <sup>2</sup>
	Female 3-core NPN	CO8.3-2/LN	3	4A/30V	2m	0.25mm <sup>2</sup>
	Female 4-core PNP	CO8.4-2/L	4	4A/30V	2m	0.25mm <sup>2</sup>
	Female 4-core NPN	CO8.4-2/LN	4	4A/30V	2m	0.25mm <sup>2</sup>
PUR	Female 3-core	CO8.3-2/P	3	4A/60V	2m	0.25mm <sup>2</sup>
	Female 4-core	CO8.4-2/P	4	4A/30V	2m	0.25mm <sup>2</sup>
	Female 3-core PNP	CO8.3-2/L/P	3	4A/30V	2m	0.25mm <sup>2</sup>
	Female 3-core NPN	CO8.3-2/LN/P	3	4A/30V	2m	0.25mm <sup>2</sup>
	Female 4-core PNP	CO8.4-2/L/P	4	4A/30V	2m	0.25mm <sup>2</sup>
	Female 4-core NPN	CO8.4-2/LN/P	4	4A/30V	2m	0.25mm <sup>2</sup>
PVC Shielded	Female 3-core	CO8.3-2/WS	3	4A/60V	2m	0.25mm <sup>2</sup>
	Female 4-core	CO8.4-2/WS	4	4A/30V	2m	0.25mm <sup>2</sup>
PUR Shielded	Female 3-core	CO8.3-2/WSP	3	4A/60V	2m	0.25mm <sup>2</sup>
	Female 4-core	CO8.4-2/WSP/P	4	4A/30V	2m	0.25mm <sup>2</sup>

Product with LED	PNP 3-core	NPN 3-core	PNP 4-core	NPN 4-core
				

## Single-ended I/O Cordsets-M8 (Straight-male)

Type Code							
	Cable jacket	Description	Type	Pin	Rated current/voltage	Cable length	Wire section
	PVC	Male 3-core	C8.3-2	3	4A/60V	2m	0.25mm <sup>2</sup>
		Male 4-core	C8.4-2	4	4A/30V	2m	0.25mm <sup>2</sup>
	PUR	Male 3-core	C8.3-2/P	3	4A/60V	2m	0.25mm <sup>2</sup>
		Male 4-core	C8.4-2/P	4	4A/30V	2m	0.25mm <sup>2</sup>
	PVC Shielded	Male 3-core	C8.3-2/WS	3	4A/60V	2m	0.25mm <sup>2</sup>
		Male 4-core	C8.4-2/WS	4	4A/30V	2m	0.25mm <sup>2</sup>
	PUR Shielded	Male 3-core	C8.3-2/WS/P	3	4A/60V	2m	0.25mm <sup>2</sup>
		Male 4-core	C8.4-2/WS/P	4	4A/30V	2m	0.25mm <sup>2</sup>


## Single-ended I/O Cordsets-M8 (Angled-female)

Type Code						
Cable jacket	Description	Type	Pin	Rated current/voltage	Cable length	Wire section
PVC	Female 3-core	CBO8.3-2	3	4A/60V	2m	0.25mm <sup>2</sup>
	Female 4-core	CBO8.4-2	4	4A/30V	2m	0.25mm <sup>2</sup>
	Female 3-core PNP	CBO8.3-2/L	3	4A/30V	2m	0.25mm <sup>2</sup>
	Female 3-core NPN	CBO8.3-2/LN	3	4A/30V	2m	0.25mm <sup>2</sup>
	Female 4-core PNP	CBO8.4-2/L	4	4A/30V	2m	0.25mm <sup>2</sup>
	Female 4-core NPN	CBO8.4-2/LN	4	4A/30V	2m	0.25mm <sup>2</sup>
PUR	Female 3-core	CBO8.3-2/P	3	4A/60V	2m	0.25mm <sup>2</sup>
	Female 4-core	CBO8.4-2/P	4	4A/30V	2m	0.25mm <sup>2</sup>
	Female 3-core PNP	CBO8.3-2/L/P	3	4A/30V	2m	0.25mm <sup>2</sup>
	Female 3-core NPN	CBO8.3-2/LN/P	3	4A/30V	2m	0.25mm <sup>2</sup>
	Female 4-core PNP	CBO8.4-2/L/P	4	4A/30V	2m	0.25mm <sup>2</sup>
	Female 4-core NPN	CBO8.4-2/LN/P	4	4A/30V	2m	0.25mm <sup>2</sup>
PVC Shielded	Female 3-core	CBO8.3-2/WS	3	4A/60V	2m	0.25mm <sup>2</sup>
	Female 4-core	CBO8.4-2/WS	4	4A/60V	2m	0.25mm <sup>2</sup>
PUR Shielded	Female 3-core	CBO8.3-2/WS/P	3	4A/60V	2m	0.25mm <sup>2</sup>
	Female 4-core	CBO8.4-2/WS/P	4	4A/60V	2m	0.25mm <sup>2</sup>




Product with LED	PNP 3-core	NPN 3-core	PNP 4-core	NPN 4-core



## Single-ended I/O Cordsets-M8 (Angled-male)

Type Code							
	Cable jacket	Description	Type	Pin	Rated current/voltage	Cable length	Wire section
	PVC	Male 3-core	CB8.3-2	3	4A/60V	2m	0.25mm <sup>2</sup>
		Male 4-core	CB8.4-2	4	4A/30V	2m	0.25mm <sup>2</sup>
	PUR	Male 3-core	CB8.3-2/P	3	4A/60V	2m	0.25mm <sup>2</sup>
		Male 4-core	CB8.4-2/P	4	4A/30V	2m	0.25mm <sup>2</sup>
	PVC Shielded	Male 3-core	CB8.3-2/WS	3	4A/60V	2m	0.25mm <sup>2</sup>
		Male 4-core	CB8.4-2/WS	4	4A/30V	2m	0.25mm <sup>2</sup>
	PUR Shielded	Male 3-core	CB8.3-2/WS/P	3	4A/60V	2m	0.25mm <sup>2</sup>
		Male 4-core	CB8.4-2/WS/P	4	4A/30V	2m	0.25mm <sup>2</sup>



## Double-ended I/O Connector-M8 (female) to M8 (male)

Type Code							
	Cable jacket	Description	Type	Pin	Rated current/voltage	Cable length	Wire section
	PVC	3-core straight to straight	CO8.3-2-C8.3	3	4A/60V	2m	0.25mm <sup>2</sup>
		3-core straight to angled	CO8.3-2-CB8.3	3	4A/60V	2m	0.25mm <sup>2</sup>
		4-core straight to straight	CO8.4-2-C8.4	4	4A/30V	2m	0.25mm <sup>2</sup>
		4-core straight to angled	CO8.4-2-CB8.4	4	4A/30V	2m	0.25mm <sup>2</sup>
	PUR	3-core straight to straight	CO8.3-2-C8.3/P	3	4A/60V	2m	0.25mm <sup>2</sup>
		3-core straight to angled	CO8.3-2-CB8.3/P	3	4A/60V	2m	0.25mm <sup>2</sup>
		4-core straight to straight	CO8.4-2-C8.4/P	4	4A/30V	2m	0.25mm <sup>2</sup>
		4-core straight to angled	CO8.4-2-CB8.4/P	4	4A/30V	2m	0.25mm <sup>2</sup>

## Double-ended I/O Connector-M8 (female) to M8 (male)



Type Code						
Cable jacket	Description	Type	Pin	Rated current/voltage	Cable length	Wire section
	3-core angled to straight	CBO8.3-2-C8.3	3	4A/60V	2m	0.25mm <sup>2</sup>
	3-core angled to angled	CBO8.3-2-CB8.3	3	4A/60V	2m	0.25mm <sup>2</sup>
	4-core angled to straight	CBO8.4-2-C8.4	4	4A/30V	2m	0.25mm <sup>2</sup>
	4-core angled to angled	CBO8.4-2-CB8.4	4	4A/30V	2m	0.25mm <sup>2</sup>
	3-core angled to straight	CBO8.3-2-C8.3/P	3	4A/60V	2m	0.25mm <sup>2</sup>
	3-core angled to angled	CBO8.3-2-CB8.3/P	3	4A/60V	2m	0.25mm <sup>2</sup>
	4-core angled to straight	CBO8.4-2-C8.4/P	4	4A/30V	2m	0.25mm <sup>2</sup>
	4-core angled to angled	CBO8.4-2-CB8.4/P	4	4A/30V	2m	0.25mm <sup>2</sup>

## Double-ended I/O Cordsets-M8 (female) to M12 (male)


Type Code							
	Cable jacket	Description	Type	Pin	Rated current/voltage	Cable length	Wire section
	PVC	3-core straight to straight	CO8.3-2-C12.3	3	4A/60V	2m	0.25mm <sup>2</sup>
		3-core straight to angled	CO8.3-2-CB12.3	3	4A/60V	2m	0.25mm <sup>2</sup>
		4-core straight to straight	CO8.4-2-C12.4	4	4A/30V	2m	0.25mm <sup>2</sup>
		4-core straight to angled	CO8.4-2-CB12.4	4	4A/30V	2m	0.25mm <sup>2</sup>
	PUR	3-core straight to straight	CO8.3-2-C12.3/P	3	4A/60V	2m	0.25mm <sup>2</sup>
		3-core straight to angled	CO8.3-2-CB12.3/P	3	4A/60V	2m	0.25mm <sup>2</sup>
		4-core straight to straight	CO8.4-2-C12.4/P	4	4A/30V	2m	0.25mm <sup>2</sup>
		4-core straight to angled	CO8.4-2-CB12.4/P	4	4A/30V	2m	0.25mm <sup>2</sup>



## Double-ended I/O Cordsets-M8 (female) to M12 (male)


Type Code							
	Cable jacket	Description	Type	Pin	Rated current/voltage	Cable length	Wire section
	PVC	3-core angled to straight	CBO8.3-2-C12.3	3	4A/60V	2m	0.25mm <sup>2</sup>
		3-core angled to angled	CBO8.3-2-CB12.3	3	4A/60V	2m	0.25mm <sup>2</sup>
		4-core angled to straight	CBO8.4-2-C12.4	4	4A/30V	2m	0.25mm <sup>2</sup>
		4-core angled to angled	CBO8.4-2-CB12.4	4	4A/30V	2m	0.25mm <sup>2</sup>
	PUR	3-core angled to straight	CBO8.3-2-C12.3/P	3	4A/60V	2m	0.25mm <sup>2</sup>
		3-core angled to angled	CBO8.3-2-CB12.3/P	3	4A/60V	2m	0.25mm <sup>2</sup>
		4-core angled to straight	CBO8.4-2-C12.4/P	4	4A/30V	2m	0.25mm <sup>2</sup>
		4-core angled to angled	CBO8.4-2-CB12.4/P	4	4A/30V	2m	0.25mm <sup>2</sup>





## Double-ended I/O Cordsets-M8 (female) to M8 (male)

Type Code							
	Cable jacket	Description	Type	Pin	Rated current/voltage	Cable length	Wire section
	PVC	3-core straight to straight LEDPNP	CO8.3-2-C8.3/L	3	4A/30V	2m	0.25mm <sup>2</sup>
		3-core straight to angled LEDPNP	CO8.3-2-CB8.3/L	3	4A/30V	2m	0.25mm <sup>2</sup>
		4-core straight to straight LEDPNP	CO8.4-2-C8.4/L	4	4A/30V	2m	0.25mm <sup>2</sup>
		4-core straight to angled LEDPNP	CO8.4-2-CB8.4/L	4	4A/30V	2m	0.25mm <sup>2</sup>
		3-core straight to straight LEDNPN	CO8.3-2-C8.3/LN	3	4A/30V	2m	0.25mm <sup>2</sup>
		3-core straight to angled LEDNPN	CO8.3-2-CB8.3/LN	3	4A/30V	2m	0.25mm <sup>2</sup>
		4-core straight to straight LEDNPN	CO8.4-2-C8.4/LN	4	4A/30V	2m	0.25mm <sup>2</sup>
		4-core straight to angled LEDNPN	CO8.4-2-CB8.4/LN	4	4A/30V	2m	0.25mm <sup>2</sup>
	PUR	3-core straight to straight LEDPNP	CO8.3-2-C8.3/L/P	3	4A/30V	2m	0.25mm <sup>2</sup>
		3-core straight to angled LEDPNP	CO8.3-2-CB8.3/L/P	3	4A/30V	2m	0.25mm <sup>2</sup>
		4-core straight to straight LEDPNP	CO8.4-2-C8.4/L/P	4	4A/30V	2m	0.25mm <sup>2</sup>
		4-core straight to angled LEDPNP	CO8.4-2-CB8.4/L/P	4	4A/30V	2m	0.25mm <sup>2</sup>
		3-core straight to straight LEDNPN	CO8.3-2-C8.3/LN/P	3	4A/30V	2m	0.25mm <sup>2</sup>
		3-core straight to angled LEDNPN	CO8.3-2-CB8.3/LN/P	3	4A/30V	2m	0.25mm <sup>2</sup>
		4-core straight to straight LEDNPN	CO8.4-2-C8.4/LN/P	4	4A/30V	2m	0.25mm <sup>2</sup>
		4-core straight to angled LEDNPN	CO8.4-2-CB8.4/LN/P	4	4A/30V	2m	0.25mm <sup>2</sup>


Product with LED	PNP 3-core	NPN 3-core	PNP 4-core	NPN 4-core





## Double-ended I/O Cordsets-M8 (female) to M8 (male)

Type Code							
	Cable jacket	Description	Type	Pin	Rated current/voltage	Cable length	Wire section
	PVC	3-core angled to straight LEDPNP	CBO8.3-2-C8.3/L	3	4A/30V	2m	0.25mm <sup>2</sup>
		3-core angled to angled LEDPNP	CBO8.3-2-CB8.3/L	3	4A/30V	2m	0.25mm <sup>2</sup>
		4-core angled to straight LEDPNP	CBO8.4-2-C8.4/L	4	4A/30V	2m	0.25mm <sup>2</sup>
		4-core angled to angled LEDPNP	CBO8.4-2-CB8.4/L	4	4A/30V	2m	0.25mm <sup>2</sup>
		3-core angled to straight LEDNPN	CBO8.3-2-C8.3/LN	3	4A/30V	2m	0.25mm <sup>2</sup>
		3-core angled to angled LEDNPN	CBO8.3-2-CB8.3/LN	3	4A/30V	2m	0.25mm <sup>2</sup>
		4-core angled to straight LEDNPN	CBO8.4-2-C8.4/LN	4	4A/30V	2m	0.25mm <sup>2</sup>
		4-core angled to angled LEDNPN	CBO8.4-2-CB8.4/LN	4	4A/30V	2m	0.25mm <sup>2</sup>
	PUR	3-core straight to straight LEDPNP	CBO8.3-2-C8.3/LP	3	4A/30V	2m	0.25mm <sup>2</sup>
		3-core straight to angled LEDPNP	CBO8.3-2-CB8.3/L/P	3	4A/30V	2m	0.25mm <sup>2</sup>
		4-core straight to straight LEDPNP	CBO8.4-2-C8.4/L/P	4	4A/30V	2m	0.25mm <sup>2</sup>
		4-core straight to angled LEDPNP	CBO8.4-2-CB8.4/L/P	4	4A/30V	2m	0.25mm <sup>2</sup>
		3-core straight to straight LEDNPN	CBO8.3-2-C8.3/LN/P	3	4A/30V	2m	0.25mm <sup>2</sup>
		3-core straight to angled LEDNPN	CBO8.3-2-CB8.3/LN/P	3	4A/30V	2m	0.25mm <sup>2</sup>
		4-core straight to straight LEDNPN	CBO8.4-2-C8.4/LN/P	4	4A/30V	2m	0.25mm <sup>2</sup>
		4-core straight to angled LEDNPN	CBO8.4-2-CB8.4/LN/P	4	4A/30V	2m	0.25mm <sup>2</sup>


Product with LED	PNP 3-core	NPN 3-core	PNP 4-core	NPN 4-core
				





## Double-ended I/O Cordsets-M8 (female) to M12 (male)

Type Code							
	Cable jacket	Description	Type	Pin	Rated current/voltage	Cable length	Wire section
	PVC	3-core straight to straight LEDPNP	CO8.3-2-C12.3/L	3	4A/30V	2m	0.25mm <sup>2</sup>
		3-core straight to angled LEDPNP	CO8.3-2-CB12.3/L	3	4A/30V	2m	0.25mm <sup>2</sup>
		4-core straight to straight LEDPNP	CO8.4-2-C12.4/L	4	4A/30V	2m	0.25mm <sup>2</sup>
		4-core straight to angled LEDPNP	CO8.4-2-CB12.4/L	4	4A/30V	2m	0.25mm <sup>2</sup>
		3-core straight to straight LEDNPN	CO8.3-2-C12.3/LN	3	4A/30V	2m	0.25mm <sup>2</sup>
		3-core straight to angled LEDNPN	CO8.3-2-CB12.3/LN	3	4A/30V	2m	0.25mm <sup>2</sup>
		4-core straight to straight LEDNPN	CO8.4-2-C12.4/LN	4	4A/30V	2m	0.25mm <sup>2</sup>
		4-core straight to angled LEDNPN	CO8.4-2-CB12.4/LN	4	4A/30V	2m	0.25mm <sup>2</sup>
	PUR	3-core straight to straight LEDPNP	CO8.3-2-C12.3/L/P	3	4A/30V	2m	0.25mm <sup>2</sup>
		3-core straight to angled LEDPNP	CO8.3-2-CB12.3/L/P	3	4A/30V	2m	0.25mm <sup>2</sup>
		4-core straight to straight LEDPNP	CO8.4-2-C12.4/L/P	4	4A/30V	2m	0.25mm <sup>2</sup>
		4-core straight to angled LEDPNP	CO8.4-2-CB12.4/L/P	4	4A/30V	2m	0.25mm <sup>2</sup>
		3-core straight to straight LEDNPN	CO8.3-2-C12.3/LN/P	3	4A/30V	2m	0.25mm <sup>2</sup>
		3-core straight to angled LEDNPN	CO8.3-2-CB12.3/LN/P	3	4A/30V	2m	0.25mm <sup>2</sup>
		4-core straight to straight LEDNPN	CO8.4-2-C12.4/LN/P	4	4A/30V	2m	0.25mm <sup>2</sup>
		4-core straight to angled LEDNPN	CO8.4-2-CB12.4/LN/P	4	4A/30V	2m	0.25mm <sup>2</sup>


Product with LED	PNP 3-core	NPN 3-core	PNP 4-core	NPN 4-core
				

## Double-ended I/O Cordsets-M8 (female) to M12 (male)

Type Code						
Cable jacket	Description	Type	Pin	Rated current/voltage	Cable length	Wire section
 PVC	3-core angled to straight LEDPNP	CBO8.3-2-C12.3/L	3	4A/30V	2m	0.25mm <sup>2</sup>
	3-core angled to angled LEDPNP	CBO8.3-2-CB12.3/L	3	4A/30V	2m	0.25mm <sup>2</sup>
	4-core angled to straight LEDPNP	CBO8.4-2-C12.4/L	4	4A/30V	2m	0.25mm <sup>2</sup>
	4-core angled to angled LEDPNP	CBO8.4-2-CB12.4/L	4	4A/30V	2m	0.25mm <sup>2</sup>
	3-core angled to straight LEDNPN	CBO8.3-2-C12.3/LN	3	4A/30V	2m	0.25mm <sup>2</sup>
	3-core angled to angled LEDNPN	CBO8.3-2-CB12.3/LN	3	4A/30V	2m	0.25mm <sup>2</sup>
	4-core angled to straight LEDNPN	CBO8.4-2-C12.4/LN	4	4A/30V	2m	0.25mm <sup>2</sup>
	4-core angled to angled LEDNPN	CBO8.4-2-CB12.4/LN	4	4A/30V	2m	0.25mm <sup>2</sup>
PUR	3-core angled to straight LEDPNP	CBO8.3-2-C12.3/L/P	3	4A/30V	2m	0.25mm <sup>2</sup>
	3-core angled to angled LEDPNP	CBO8.3-2-CB12.3/L/P	3	4A/30V	2m	0.25mm <sup>2</sup>
	4-core angled to straight LEDPNP	CBO8.4-2-C12.4/L/P	4	4A/30V	2m	0.25mm <sup>2</sup>
	4-core angled to angled LEDPNP	CBO8.4-2-CB12.4/L/P	4	4A/30V	2m	0.25mm <sup>2</sup>
	3-core angled to straight LEDNPN	CBO8.3-2-C12.3/LN/P	3	4A/30V	2m	0.25mm <sup>2</sup>
	3-core angled to angled LEDNPN	CBO8.3-2-CB12.3/LN/P	3	4A/30V	2m	0.25mm <sup>2</sup>
	4-core angled to straight LEDNPN	CBO8.4-2-C12.4/LN/P	4	4A/30V	2m	0.25mm <sup>2</sup>
	4-core angled to angled LEDNPN	CBO8.4-2-CB12.4/LN/P	4	4A/30V	2m	0.25mm <sup>2</sup>


Product with LED	PNP 3-core	NPN 3-core	PNP 4-core	NPN 4-core
	 <p>Diagram showing a 3-core PNP LED circuit. The 1+ pin is connected to the positive terminal of the first LED (GN). The 4 J pin is connected to the positive terminal of the second LED (YE). The 3- pin is connected to the positive terminal of the third LED (BU). The negative terminals of all LEDs are connected to a common ground.</p>	 <p>Diagram showing a 3-core NPN LED circuit. The 1+ pin is connected to the positive terminal of the first LED (GN). The 4 J pin is connected to the positive terminal of the second LED (YE). The 3- pin is connected to the positive terminal of the third LED (BU). The negative terminals of all LEDs are connected to a common ground.</p>	 <p>Diagram showing a 4-core PNP LED circuit. The 1+ pin is connected to the positive terminal of the first LED (GN). The 2 L pin is connected to the positive terminal of the second LED (YE). The 4 J pin is connected to the positive terminal of the third LED (RD). The 3- pin is connected to the positive terminal of the fourth LED (BU). The negative terminals of all LEDs are connected to a common ground.</p>	 <p>Diagram showing a 4-core NPN LED circuit. The 1+ pin is connected to the positive terminal of the first LED (GN). The 2 L pin is connected to the positive terminal of the second LED (YE). The 4 J pin is connected to the positive terminal of the third LED (RD). The 3- pin is connected to the positive terminal of the fourth LED (BU). The negative terminals of all LEDs are connected to a common ground.</p>

## Y Splitter M8-male to M8-female


Type Code							
	Cable jacket	Description	Type	Pin	Rated current/voltage	Cable length	Wire section
	PVC	Straight to 2 straight	ECS-E2CO8.3-2/2	4-3/3	4A/30V	2m	0.25mm <sup>2</sup>
		Straight to 2 angled	ECS-E2CBO8.3-2/2	4-3/3	4A/30V	2m	0.25mm <sup>2</sup>
	PUR	Straight to 2 straight	ECS-E2CO8.3-2/2/P	4-3/3	4A/30V	2m	0.25mm <sup>2</sup>
		Straight to 2 angled	ECS-E2CBO8.3-2/2/P	4-3/3	4A/30V	2m	0.25mm <sup>2</sup>

Wiring Diagram

Standard




## Y Splitter M8-male to M12-female



Type Code							
	Cable jacket	Description	Type	Pin	Rated current/voltage	Cable length	Wire section
	PVC	Straight to 2 straight	ECS-E2CO12.3-2/2	4-3/3	4A/30V	2m	0.25mm <sup>2</sup>
		Straight to 2 angled	ECS-E2CBO12.3-2/2	4-3/3	4A/30V	2m	0.25mm <sup>2</sup>
	PUR	Straight to 2 straight	ECS-E2CO12.3-2/2/P	4-3/3	4A/30V	2m	0.25mm <sup>2</sup>
		Straight to 2 angled	ECS-E2CBO12.3-2/2/P	4-3/3	4A/30V	2m	0.25mm <sup>2</sup>


### Wiring Diagram

### Standard





## Y Splitter M8-male to M8-female

Type Code							
	Cable jacket	Description	Type	Pin	Rated current/voltage	Cable length	Wire section
	PVC	Straight to 2 straight	PNP	ECS-E2CO8.3-2/2/L	4-3/3	4A/30V	2m 0.25mm <sup>2</sup>
		Straight to 2 angled	PNP	ECS-E2CBO8.3-2/2/L	4-3/3	4A/30V	2m 0.25mm <sup>2</sup>
		Straight to 2 straight	NPN	ECS-E2CO8.3-2/2/LN	4-3/3	4A/30V	2m 0.25mm <sup>2</sup>
		Straight to 2 angled	NPN	ECS-E2CBO8.3-2/2/LN	4-3/3	4A/30V	2m 0.25mm <sup>2</sup>
	PUR	Straight to 2 straight	PNP	ECS-E2CO8.3-2/2/L/P	4-3/3	4A/30V	2m 0.25mm <sup>2</sup>
		Straight to 2 angled	PNP	ECS-E2CBO8.3-2/2/L/P	4-3/3	4A/30V	2m 0.25mm <sup>2</sup>
		Straight to 2 straight	NPN	ECS-E2CO8.3-2/2/LN/P	4-3/3	4A/30V	2m 0.25mm <sup>2</sup>
		Straight to 2 angled	NPN	ECS-E2CBO8.3-2/2/LN/P	4-3/3	4A/30V	2m 0.25mm <sup>2</sup>






## Y Splitter M8-male to M12-female


Type Code							
	Cable jacket	Description	Type	Pin	Rated current/voltage	Cable length	Wire section
	PVC	Straight to 2 straight	PNP	ECS-E2CO12.3-2/2/L	4-3/3	4A/30V	2m 0.25mm <sup>2</sup>
		Straight to 2 angled	PNP	ECS-E2CBO12.3-2/2/L	4-3/3	4A/30V	2m 0.25mm <sup>2</sup>
		Straight to 2 straight	NPN	ECS-E2CO12.3-2/2/LN	4-3/3	4A/30V	2m 0.25mm <sup>2</sup>
		Straight to 2 angled	NPN	ECS-E2CBO12.3-2/2/LN	4-3/3	4A/30V	2m 0.25mm <sup>2</sup>
	PUR	Straight to 2 straight	PNP	ECS-E2CO12.3-2/2/L/P	4-3/3	4A/30V	2m 0.25mm <sup>2</sup>
		Straight to 2 angled	PNP	ECS-E2CBO12.3-2/2/L/P	4-3/3	4A/30V	2m 0.25mm <sup>2</sup>
		Straight to 2 straight	NPN	ECS-E2CO12.3-2/2/LN/P	4-3/3	4A/30V	2m 0.25mm <sup>2</sup>
		Straight to 2 angled	NPN	ECS-E2CBO12.3-2/2/LN/P	4-3/3	4A/30V	2m 0.25mm <sup>2</sup>

### Product with LED


#### PNP 3-core



#### NPN 3-core





## Y Splitter M8(M) to Homerun Cable

Type Code							
	Cable jacket	Description	Type	Pin	Rated current/voltage	Cable length	Wire section
	PVC	Y Splitter M8(M) to homerun cable	ECS-E2.3-2/2	4-3/3	4A/60V	2m	0.25mm <sup>2</sup>
	PUR	Y Splitter M8(M) to homerun cable	ECS-E2.3-2/2/P	4-3/3	4A/60V	2m	0.25mm <sup>2</sup>

### Wiring Diagram

### Standard





ELCO Industrie Automation GmbH

Benzstrasse 7

71720 Oberstenfeld

Deutschland

E-Mail: [info@elco-automation.de](mailto:info@elco-automation.de)



[www.elco-automation.de](http://www.elco-automation.de)

ELCO (TIANJIN) ELECTRONICS CO., LTD.

No. 12, 4th XEDA Branch Road

Xiqing Economic Development Area

Tianjin 300385, P. R. China

E-Mail: [info@elco.cn](mailto:info@elco.cn)



[www.elco-holding.com.cn](http://www.elco-holding.com.cn)